



Dimensions



CF 90

USE:

- 2-way connections with angles up to 20°-160° for most Cold Formed shapes

WORKS WITH:

EZ80, EZ88, EZ95, JZ112,
 MSZ18 312, MSZ18 340,
 MSZ18 350, MSZ18 375,
 MSZ18 406, MSZ19 340,
 MSZ19 350, MSZ19 375,
 MSZ19 406, PAZ-CF 4460,
 PAZ-CF 4470, PAZ-CF 5460,
 PAZ-CF 5470, PAZ-CF 5480,
 PAZ-CF 5560, PAZ-CF 5570,
 PAZ-CF 5580, SCZ 14,
 SCZ 16, SCZ 17, SCZ 18,
 SCZ 19, SCZ 21, SCZ 22,
 SCZ 23, SCZ 25, SCZ 26,
 SCZ 29, SCZ 30, SKZ 20,
 SKZ 22, SKZ 23, SKZ 24,
 SKZ 25, SKZ 31, SKZ 33,
 SKZ 34, SKZ 36, SKZ 38,
 XZ100, XZ105, XZ85, XZ90,
 XZ95, Z 55, Z 60, Z 65,
 Z 70, Z 75

WEIGHT:

~ 8.9 lb/ft
 ~ 13.2 kg/m

TYPICAL STEEL GRADES:

ASTM A572 Gr. 50/60
 ASTM A690
 Other steel grades
 available upon request.



For additional details and CAD files
 visit pilepro.com/cfc90